

2 INCH WATER CURB BOXES

- The slip-type design protects the service from downward pressure. The box absorbs the pressure from above. If all the downward adjustment is used and additional pressure causes the box to collapse further, the bell area will collapse before damaging the service. This is a SAFE installation.
- Easily adjusts to grade level. No need to dig when grade changes. Just step-on to push down or pry it up.
- Heat formed dimples give the box strong tension. The tension and flange under the lid keeps the upper tube from settling.
- A full throat/unobstructed upper tube, allows more room to operate the key.
- Made from SUPERIOR GRADE ABS plastic. It's long lasting and won't rust, rot or corrode.
- Minneapolis thread bushing in 2" or 1 ½" sizes available in straight boxes with no bell area.
- Choose from cast iron or plastic lids.
- Features a one-piece locking lid. No parts to lose.
- Available with lids marked "WATER" or "SEWER".
- Customized lids available for an additional charge.
- Box design offers 2" cast iron collar, 2" cast iron light duty, flanged, straight or 5" cast iron heavy duty upper tubes.
- A permanent "Real" magnet is in every upper tube. A metal reflector is included in every plastic lid for easy location with electronic locators.
- Extensions are available, or upper tubes can be used as extensions.
- Snap-on bells available upon request.



HOW TO ORDER SUPERIOR GRADE WATER CURB BOXES

Choose from the following categories to build the curb box best suited to your personal needs. Many options are available so please look this over closely, we don't want you to miss a thing!

| | | | |
|--|---------------------------------|--|---|
| ONE = LID LETTERING S = Sewer W = Water | TWO = BOX SIZE 2 = 2" | THREE = LID MATERIAL I = Iron P = Plastic Only use these codes with Group Four – Code L I3 = Iron (Flush) IT = Iron (Threaded) | FOUR = UPPER TUBE STYLE C = Plastic Flange Top with Cast Iron Collar F = Plastic Flange Top H = Heavy Duty Iron Flange Top S = Straight Top Flange L = Light Duty Iron Flange Top |
| <u>FIVE = ADJUSTABLE RANGE</u> - Measured from the top of the box to the bottom of the box. | | | |
| If you chose <u>CODE C, F, L or S</u> from <u>GROUP FOUR</u> , choose from the following codes: A = 18 $\frac{5}{8}$ " - 24" B = 20 $\frac{5}{8}$ " - 28" C = 22 $\frac{5}{8}$ " - 32" D = 24 $\frac{5}{8}$ " - 36" E = 26 $\frac{1}{8}$ " - 39" F = 27 $\frac{5}{8}$ " - 42" G = 30 $\frac{5}{8}$ " - 48" H = 37 $\frac{1}{2}$ " - 62" K = 51 $\frac{1}{2}$ " - 76" L = 63 $\frac{1}{2}$ " - 88" M = 75 $\frac{1}{2}$ " - 100" | | If you chose <u>CODE H</u> from <u>GROUP FOUR</u> , choose from the following codes: A = 21 $\frac{3}{8}$ " - 26 $\frac{3}{4}$ " B = 23 $\frac{3}{8}$ " - 30 $\frac{3}{4}$ " C = 25 $\frac{3}{8}$ " - 34 $\frac{3}{4}$ " D = 27 $\frac{3}{8}$ " - 38 $\frac{3}{4}$ " E = 28 $\frac{7}{8}$ " - 41 $\frac{3}{4}$ " F = 30 $\frac{3}{8}$ " - 44 $\frac{3}{4}$ " G = 33 $\frac{3}{8}$ " - 50 $\frac{3}{4}$ " H = 40 $\frac{3}{8}$ " - 64 $\frac{3}{4}$ " K = 54 $\frac{1}{4}$ " - 78 $\frac{3}{4}$ " L = 66 $\frac{1}{4}$ " - 90 $\frac{3}{4}$ " M = 78 $\frac{1}{4}$ " - 102 $\frac{3}{4}$ " | |



SIX = SPECIAL BELLS**CODES VALVE APPLICATION**

- 50 = Snap-On Bell for a Variety of Water Valves
 52 = Water and Sewer Arch for the 1¼" Cepex Valve and other larger curb valves
 53 = Minneapolis Base for 2" Threads
 54 = Minneapolis Base for 1½" Threads
 57 = Round Bell

SEVEN = LID COLOR

(Black is Standard)

- A = Black D = Red
 B = Blue E = White
 C = Green F = Orange

EIGHT = FLANGE COLOR

(Silver is Standard)

- G = White
 H = Yellow
 J = Black

NINE = TRACER WIRE HOLES

(Not Available On Heavy Duty Boxes)

- K = Tracer Wire Holes

TEN = VENT HOLE

L = One 3/8" Vent Hole (Mandatory Group Four Codes C, F and H)

N = Two 3/8" Vent Holes

ELEVEN = MAGNET (One Magnet Located in the Flange is Standard, except on Group Four – Code L)

P = No Magnet at All

Q = One Magnet in the Lower Tube

R = One Magnet Located in the Flange and One in the Lower Tube

FOR OTHER OPTIONS OR VARIATIONS, PLEASE CONSULT THE FACTORY.

